



**北京环瑞商贸有限公司**

BEIJING HUANRUI Co., Ltd

# VP-220 T (Y)型過濾器

## T (Y) type Strainer

- Easy to disassemble and clean the screen
- Screen specification:  
T type-SUS 304 / 316L,  
40 / 20 mesh/cm<sup>2</sup>  
Y type-60 / 40 / 20 mesh/cm<sup>2</sup>

- 濾網拆卸清洗方便
- 濾網規格：  
T型-SUS 304 / 316L,  
40 / 20 mesh/cm<sup>2</sup>  
Y型-60 / 40 / 20 mesh/cm<sup>2</sup>

Type 品號	Size 尺寸	Standard 規格	Material 材質	Gasket / Seal 墊片	End type 接口
VP-220 T type	2"~8"	ANSI, JIS	PVC	NR	Flanged
VP-220 Y type	1/2"~2"	ANSI, JIS, DIN	PVC	NR	Union, Socket, Flanged
VP-221 T type	2"~8"	ANSI, JIS	CPVC	EPDM, FPM	Flanged
VP-221 Y type	1/2"~2"	ANSI, JIS, DIN	CPVC	EPDM, FPM	Union, Socket, Flanged



## T-type Strainer DIM.

Nom.	SIZE	50mm (2")	65mm (2-1/2")	80mm (3")	100mm (4")	150mm (6")	200mm (8")
	n-øe	JIS	4-ø19	4-ø19	8-ø19	8-ø19	8-ø23
	ANSI	4-ø19	4-ø19	4-ø19	8-ø19	8-ø22	8-ø22
	DIN	4-ø18	4-ø18	4-ø18	8-ø18	8-ø23	8-ø23
L		200	240	260	300	400	500
D	JIS	155	175	185	210	285	330
	ANSI	152	178	191	229	285	343
	DIN	165	185	200	220	285	343
D1	JIS	120	140	150	175	240	290
	ANSI	120	140	152.4	190.5	241	298
	DIN	125	145	160	180	240	295
T		20	22	22	24	26	30
H		166	170.5	170	216	286	336

NO.	PART	MATERIAL	QTY
1	BODY	UPVC, CPVC	1
2	BONNET	UPVC, CPVC	1
3	90° ELL	UPVC, CPVC	1
4	INNER BODY	UPVC, CPVC	1
5	OUTER BODY	UPVC, CPVC	1
6	GASKET	EPDM, FPM	1
7	FILTER	SUS304 or 316L	1

## Y-type Strainer (Flanged) DIM.

Nom.	SIZE	15mm (1/2")	20mm (3/4")	25mm (1")	32mm (1-1/4")	40mm (1-1/2")	50mm (2")
	D	JIS	89	98	108	117	127
	ANSI	95	100	125	135	140	155
D1	JIS	60	70	79	89	98	121
	ANSI	70	75	90	100	105	120
L	JIS	154	170	200	245	250	290
	ANSI	160	175	202	245	247	292
H	JIS	119	131	157	190	194	224
	ANSI	122	132	166	199	200	225
T	JIS	11.1	12.7	14.3	16	17.5	19.1
	ANSI	14	15	15	16	16	20
n-øe	JIS	4-16	4-16	4-16	4-16	4-16	4-19
	ANSI	4-15	4-15	4-19	4-19	4-19	4-19

## Y-type Strainer (Union) DIM.

Nom.	SIZE	15mm (1/2")	20mm (3/4")	25mm (1")	32mm (1-1/4")	40mm (1-1/2")	50mm (2")
	D		46	55	66	82	98
ANSI	d2	21.23	26.57	33.27	42.04	48.11	60.17
	d1	21.54	26.87	33.65	42.42	48.56	60.63
	l	22.22	25.4	28.58	31.75	34.93	38.1
JIN	d2	21.7	25.7	31.67	37.57	47.54	59.44
	d1	22.3	26.3	32.33	38.43	48.46	60.56
	l	22.2	25.4	28.6	31.8	34.9	38.1
DIN	d2	20.1	25.1	32.1	40.1	50.1	63.1
	d1	20.3	25.3	32.3	40.3	50.3	63.3
	l	16	19	22	26	31	38
L		192	221	248	325	333	372
L1		54	62	69	85	89	95
H		92	111	128	160	170	203

## Y-type Strainer (Spigot) DIM.

Nom.	SIZE	15mm (1/2")	20mm (3/4")	25mm (1")	32mm (1-1/4")	40mm (1-1/2")	50mm (2")
	D		30	36	44	61	61
ANSI	d2	21.23	26.57	33.27	42.04	48.11	60.17
	d1	21.54	26.87	33.65	42.42	48.56	60.63
	l	22.22	25.4	28.58	31.75	34.93	38.1
L		95	109	127	170	170	193
H		66.5	77	90.7	122.7	122.7	143.8

