



**HUANRUI**

**北京环瑞商贸有限公司**

BEIJING HUANRUI Co., Ltd

# VP-480 .490 彈簧式 (終端) 逆止閥

## Spring Check (Foot) Valve

- Pressure rating: 150 PSI
- Minimum flow pressure : 2 PSI
- Install with flow direction arrow indication
- Low cost / maintenance operation

- 工作壓力：150 PSI
- 最低開啓壓力：2 PSI
- 依流向箭頭指示安裝
- 球體逆止設計，密閉性佳

Type 品號	Size 尺寸	Standard 規格	Material 材質	Seal 止漏墊	Spring 彈簧	End type 接口
VP-480	1/2"~2"	ANSI, JIS, DIN	PVC	EPDM, FPM	US 304	Socket, Threaded
VP-490	1/2"~2"	ANSI, JIS, DIN	PVC	EPDM, FPM	US 304	Socket, Threaded



Nom.	SIZE	15mm (1/2")	20mm (3/4")	25mm (1")	32mm (1-1/4")	40mm (1-1/2")	50mm (2")
	thd./in	NPT	14	14	11.5	11.5	11.5
	BSPT	14	14	11	11	11	11
JIS	d2	21.70	25.70	31.67	37.57	47.54	59.44
	d1	22.30	26.30	32.33	38.43	48.46	60.56
ANSI	d2	21.23	26.57	33.27	42.04	48.11	60.17
	d1	21.54	26.87	33.65	42.42	48.56	60.63
DIN	d2	20.1	25.1	32.1	40.1	50.1	63.1
	d1	20.3	25.3	32.3	40.3	50.3	63.3
	d	17	21	28	35	39	52
	D	56	56	73	91	91	107
	D1	35	35	45	52	60	73
	D2	38	38	48	55	63	76
	H	105	105	133	151	151	178
	I	17.48	18.26	22.22	23.82	27.38	29.36

NO.	PART	MATERIAL	Q'TY
1	UPPER BODY	PVC	1
2	LOWER BODY	PVC	1
3	SPIGOT	PVC	1
4	CONNECTOR SEAT	PVC	1
5	SPRING	SUS 304	1
6	SEAL	EPDM	1

Nom.	SIZE	15mm (1/2")	20mm (3/4")	25mm (1")	32mm (1-1/4")	40mm (1-1/2")	50mm (2")
	thd./in	NPT	14	14	11.5	11.5	11.5
	BSPT	14	14	11	11	11	11
JIS	d2	21.70	25.70	31.67	37.57	47.54	59.44
	d1	22.30	26.30	32.33	38.43	48.46	60.56
ANSI	d2	21.23	26.57	33.27	42.04	48.11	60.17
	d1	21.54	26.87	33.65	42.42	48.56	60.63
DIN	d2	20.1	25.1	32.1	40.1	50.1	63.1
	d1	20.3	25.3	32.3	40.3	50.3	63.3
	d	17	21	28	35	39	52
	D	60	60	83	83	110	124
	D1	35	35	45	52	60	73
	D2	38	38	48	55	63	76
	H	123	123	147	170	170	198
	I	17.48	18.26	22.22	23.82	27.38	29.36

NO.	PART	MATERIAL	Q'TY
1	BODY	PVC	1
2	FILTER	PVC	1
3	SPIGOT	PVC	1
4	CONNECTOR SEAT	PVC	1
5	SPRING	SUS 304	1
6	SEAL	EPDM	1

